

■ HM系列标准配置表 Standard Features

项目	ITEM	HM8	HM12	HM18	HM30	HM50	HM90	HM100	HM130	HM160	HM200	HM280	HM400
头板冷却水	Cooling water on foxed platen	—	—	—	●	●	●	●	●	●	●	●	●
自动喷雾1组	Auto spray 1 set	●	●	●	●	●	●	●	●	●	●	●	●
机械手	Robot	●	●	●	●	●	●	○	○	○	○	○	○
抽芯1组	Core 1 set	○	○	○	○	○	●	●	●	●	●	●	●
额外抽芯装置	Extra core pulling device	○	○	○	○	○	○	○	○	○	○	○	○
“0” 位压射位置	Home Injection position	●	●	●	●	●	●	●	●	●	●	●	●
油压升降台	Hydraulic lifter	—	—	—	○	○	○	○	●	●	●	●	●
前门电动	Pneumatic safety door (front)	—	—	—	○	○	○	○	○	○	●	●	●
抽芯吉制及连线	Core limit switch 2 sets	○	○	○	○	○	○	○	○	○	●	●	●

“●” 表示标准配置； “○” 表示选配项目； “—” 表示无。

■ 备选配置 Configuration Options

- 电加热熔炉
 - 压射位置采用非接触式脉冲检测
 - 刹车功能
 - 锁模力显示
 - 特殊射料位置
 - 液压升降装置
 - 自动换模装置
 - 电（气）动安全门
 - 射料曲线显示监控
- Electric melting furnace
 - Injection position adopts non-contact pulse detector
 - Brake function
 - Clamping force display
 - Special injection position
 - Hydraulic lifting device
 - Automatic die change device
 - Pneumatic (electrical) safety door
 - Shot curve display and monitor